



LOCKING PIN
Enables a secure head closing.

XCG40

HYDRAULIC HEAD GUILLOTINE CABLES CUTTER

700
bar

> Force, stroke, capacities same as the **CG40** manual tool and battery tool **BCP040G**.

TYPE OF CABLES

copper, aluminum and steel

MAX. PASSAGE

Ø 40 mm

(depending on cables)



NEW REINFORCED BLADES

Increase blades life time (> specifically for steel cuts).



IDENTICAL BLADE & COUNTER BLADE

Improve the cable cutting.



INTERCHANGEABLE BLADES

Easy to replace.

FORCE

88 kN

DIMENSIONS (L x l x h in mm)

285 x 85 x 105

WEIGHT (without protection kit)

4.300 kg



PROTECTION KIT

> As an option.



FITTINGS & HOSES

> Refer to **PAGE 67**.

	TYPE OF CABLES	MAX. HARDNESS	MAX. Ø OF CUT (mm) *	
CABLES	Copper	< 40 daN/mm ²	Ø 32 (630 mm ²)	
	Aluminum	< 20 daN/mm ²	Ø 40	
	Almelec	< 34 daN/mm ²	Ø 40	
	Steel		< 180 daN/mm ²	7 x Ø 3.0 (= Ø 9.0)
				19 x Ø 2.1 (= Ø 10.5)
				19 x Ø 2.3 (= Ø 11.5)
	Multi-steel strands	< 180 daN/mm ²	Ø 18 (strands quantities : 200)	
	ACSR (medium hard steel)		< 180 daN/mm ²	26 x Ø 2.50 + 7 x Ø 1.95 (= Ø 15.85)
				26 x Ø 3.06 + 7 x Ø 2.38 (= Ø 19.38)
				26 x Ø 3.60 + 7 x Ø 2.80 (= Ø 22.80)
BARS	Steel	< 60 daN/mm ²	Ø 18	
		< 42 daN/mm ²	Ø 20	
		< 30 daN/mm ²	Ø 30	
	Copper	< 25 daN/mm ²	Ø 32	
		< 16 daN/mm ²	Ø 40	
		Aluminum	< 16 daN/mm ²	Ø 40

* Other dimensions and cables to be approved with tests.



Do not use this tool on live cables.