

HYDRAULIC POWER PACK 20 l/min



ASPID is a professional power pack with 11 Hp diesel engine - recoil and battery start. The pack supplies a flow of 20 L/min at 145 Bar pressure so it can power tools of group C of EHTMA standard.

Every part of **ASPID** is manufactured to give the maximum of performances, reliability and transportability. The points of strength are the quietness the robustness and economy that make its use ideal in the urban maintenance and in the professional works in general.

The new design and the numerous exclusive features make point by point **ASPID** one of the best products available today on the market.

ADVANTAGES

- ROBUST FRAME IN STAINLESS STEEL TUBE WITH BENDABLE LIFTING EYE
- POWER ON DEMAND ACCELERATION RAM LIMITS NOISE AND CONSUMPTION
- QUICK COUPLERS INSTALLED ON SWIVEL FITTINGS PROTECT AGAINST IMPACTS
- OIL COOLER INSTALLED ON SUCTION LINE AVOIDS DAMAGEFUL PRESSURE PULSATIONS
- HIGH EFFICIENCY OIL TEMPERATURE CONTROL IDEAL FOR TROPICAL CLIMATES
- PARTS ARE SUSPENDED ON SILENT BLOCKS TO LIMIT NOISE AND VIBRATIONS
- FRONT RETRACTABLE HANDLE PLUS LATERAL AND REAR BENDING HANDLES ASSURE CONVENIENT GRASP IN ANY SITUATION

ENGINE CHARACTERISTICS

| | |
|-------------|--------------------|
| ENGINE TYPE | YANMAR DIESEL |
| POWER | 11 HP |
| STARTING | RECOIL AND BATTERY |

WEIGHT AND DIMENSION

| | |
|---------------------|-------|
| WEIGHT WITH LIQUIDS | 85 Kg |
| HEIGHT | 65 cm |
| LENGHT | 85 cm |
| WIDTH | 60 cm |

HYDRAULIC CHARACTERISTICS

| | |
|-------------------|----------|
| FLOW | 20 l/min |
| PRESSURE MAX | 145 BAR |
| OIL TANK CAPACITY | 10 l. |
| STD HOSE LENGTH | 7 mt |