




**LOCKING PIN**  
 Enables a secure head closing.



# XCG45

## HYDRAULIC HEAD GUILLOTINE CABLES CUTTER



**TYPE OF CABLES**




copper, aluminum, steel, stainless steel and ACSR

**MAX. PASSAGE**

**Ø 45 mm**  
 (depending on cables)



> Force, stroke, capacities same as the battery tool **BCP045G**.

-  **NEW REINFORCED BLADES**  
 Increase blades life time (> specifically for steel cuts).
-  **IDENTICAL BLADE & COUNTER BLADE**  
 Improve the cable cutting.
-  **INTERCHANGEABLE BLADES**  
 Easy to replace.

<b>FORCE</b>	130 kN
<b>DIMENSIONS</b> (L x l x h in mm)	320 x 65 x 110
<b>WEIGHT</b> (without protection kit)	4.900 kg

-  **PROTECTION KIT**  
 > As an option.
-  **FITTINGS & HOSES**  
 > Refer to **PAGE 67**.

**MAX. CUTTING CAPACITIES**

\* Other dimensions and cables to be tested and validated.

	TYPE OF CABLES	MAX. HARDNESS	MAX. Ø OF CUT (mm) *	
<b>CABLES</b>	Copper	< 30 daN/mm <sup>2</sup>	Ø 45	
	Aluminum	< 20 daN/mm <sup>2</sup>	Ø 45	
	Almelec	< 34 daN/mm <sup>2</sup>	Ø 45	
	Steel	< 180 daN/mm <sup>2</sup>	7 x Ø 3.0 (= Ø 9.0) 19 x Ø 2.1 (= Ø 10.5) 19 x Ø 2.3 (= Ø 11.5)	
	Multi-steel strands	< 180 daN/mm <sup>2</sup>	Ø 18 (strands quantities: 200)	
	ACSR	< 180 daN/mm <sup>2</sup>	26 x Ø 2.50 + 7 x Ø 1.95 (= Ø 15.85) 26 x Ø 3.06 + 7 x Ø 2.38 (= Ø 19.38) 26 x Ø 3.60 + 7 x Ø 2.80 (= Ø 22.80) 54 x Ø 3.50 + 19 x Ø 2.10 (= Ø 31.50) 54 x Ø 4.36 + 19 x Ø 2.62 (= Ø 39.20)	
	Inox	<b>&gt; please contact us.</b>		
	<b>BARS</b>	Steel	< 60 daN/mm <sup>2</sup> < 42 daN/mm <sup>2</sup>	Ø 18 Ø 20
		Copper	< 30 daN/mm <sup>2</sup> < 25 daN/mm <sup>2</sup>	Ø 30 Ø 32
		Aluminum	< 16 daN/mm <sup>2</sup>	Ø 45



Do not use this tool on live cables.