



**LOCK**  
Enables quick opening and closing head.

# XCG55

## HYDRAULIC HEAD GUILLOTINE CABLES CUTTER

700 bar

> Force, stroke, capacities same as the **CG55** manual tool and the battery tool **BCP055G**.

**TYPE OF CABLES**  
copper and aluminum

**MAX. PASSAGE**  
Ø 55 mm





-  **NEW COUNTER BLADE**  
Decreases cable distortion when cutting.
-  **SHARP BLADE & COUNTER BLADE**  
Improve the cable cutting.
-  **LIGHT & POWERFUL**  
Refer to cutting capacities.

**WIDE OPENING**  
Easy for cables passage.



<b>FORCE</b>	43 kN
<b>DIMENSIONS</b> (L x l x h in mm)	300 x 55 x 110
<b>WEIGHT</b> (without protection kit)	3 kg

-  **PROTECTION KIT**  
> As an option.
-  **FITTINGS & HOSES**  
> Refer to **PAGE 67**.

### MAX. CUTTING CAPACITIES

\* Other dimensions and cables to be tested and validated.

	TYPE OF CABLES	MAX. HARDNESS	SECTIONS	MAX. Ø OF CUT *
<b>CABLES</b>	Copper leads cables		4 x 185 mm <sup>2</sup> or 630 mm <sup>2</sup> max.	
	Underground aluminum		3 x 240 + 1 x 95 mm <sup>2</sup>	Ø 51 mm
	Telephone cables			Ø 55 mm
<b>BARS</b>	Round annealed copper	< 20 daN/mm <sup>2</sup>		Ø 16 - 18 mm
	Round annealed aluminum (A5)	< 16 daN/mm <sup>2</sup>		Ø 20 - 25 mm



Do not use this tool on live cables.